



When Ordering,
Specify
With or Without
HINGED COVER

Available in the following connections:
 BUWT WELD, SOCKET WELD, SIL-BRAZE, THREADED (NPT),
 CAST FLANGE, and WELDED STEEL SLIP-ON FLANGE.
 Flanges Drilled 150# Commercial unless specified otherwise.

MATERIALS

1	Body	Cast Steel, Iron,
2	Flange	(Galv. or Black)
3	Seat	Cast Bronze, Alum,
4	Spacer	Stainless Steel,
5	Cover	Monel, etc.
6	Float	Cu, S.S., or MONEL
7	Float Rest Screen	Stainless Steel,
8	Flame Screen	Brass, or Monel
9	Protective Screen	
10	Screws & Washers	Brass, Stainless
11	Hinge Pin	Stainless Steel
12	Toggle Assembly	

DIMENSIONS -- INCHES

	A	B ₁	B	C	D	E
(IPS)						
3/4	3 1/4	4-5/8	5 1/2	4 1/2	1 1/4	
1	3 1/4	4-5/8	5 1/2	4 1/2	1 1/4	
1 1/2	3 1/2	4-5/8	5 1/2	4 1/2	1 1/4	
2	5 1/2	7 1/4	7 1/2	6-3/4	2 1/2	
2 1/2	5 1/2	7 1/4	7 1/2	6-3/4	2 1/2	
3	5 1/2	7 1/4	7 1/2	6-3/4	2 1/2	
3 1/2	7	9	9	8 1/4	3	
4	7 1/4	9	9	8 1/4	4	
5	9	10	10	9 1/4	5	

GALVANIZED
STEEL AND
BRONZE IN
STOCK

KINGS POINT MACHINERY,
9936 Gould Street
Oakland, CA 94603
(510) 638-2712
FAX (510) 638-3339

TITLE
INVERTED VENT CHECK VALVE
 3/4" IPS through 5" IPS

DRAWN BY GRW	CHECKED BY DCW	SCALE NTS
APPROVED	DATE 3-9-87	DRAWING NO. 1027
	REV. 0	SHEET 1 of 1